

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number  
**WO 2005/014984 A2**

(51) International Patent Classification<sup>7</sup>: **F01M 13/00**

Tadeu [BR/BR]; Rua Socrates, 625 - 102/3, Vila Sofia,  
04671-071 São Paulo - SP (BR).

(21) International Application Number:  
PCT/BR2004/000140

(74) Agent: **DANNEMANN, SIEMSEN, BIGLER &  
IPANEMA**; Caixa Postal 2142, Rua Marquês de Olinda,  
70, 22251-040- Rio de Janeiro- RJ (BR).

(22) International Filing Date: 4 August 2004 (04.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PI 0302741-4 6 August 2003 (06.08.2003) BR

(71) Applicant (for all designated States except US): **INTER-  
NATIONAL ENGINES SOUTH AMERICA LTDA.**  
[BR/BR]; Estrada dos Casas, 3155, 09840-000 São  
Bernardo do Campo - SP (BR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(72) Inventor; and

(75) Inventor/Applicant (for US only): **MINETTO, Roberto,**

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: AN INTERNAL COMBUSTION ENGINE AND AN ENGINE HEAD



(57) Abstract: The present invention relates to an internal combustion engine comprising at least one engine block (2) and at least one engine head (3) associated to the block. The block (2) comprises at least one first end (4) provided with a first cavity (5) for receiving a crankshaft, at least one second end portion (6) associated to the head (3), and at least one first through channel (7) provided with a first end (7') located in the first cavity (5) and a second end (7'') located in the second end portion (6). The head (3) comprises at least one first end portion (11), a second end portion (12) opposite the first one, and at least one second cavity (9) for positioning mechanical components. The head (3) and the block (2) are associated by cooperation between the first end portion (11) of the head (3) and the second end portion (6) of the block (2), the head (3) having additionally at least one second through channel (10) provided with a first end (10') located at its end portion (11) and a second end (10''), the first end (10') of the second through channel (10) cooperating with the second end (7'') of the first through channel (7) of the block (2) and the second end (10'') of the second through channel (10) being non-communicant with the second cavity (9).

BEST AVAILABLE COPY

WO 2005/014984 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *without international search report and to be republished upon receipt of that report*